

D3200 1080p 2 Megapixel Mini Dome IP Camera



- Megapixel 1080p Full HD resolution
- Multiple H.264, Motion JPEG and MPEG-4 video streams
- MicroSD card slot
- Power over Ethernet
- Ultra-compact
- Screwless 3-axis angle adjustment for easy installation on wall or ceiling
- Supports True Plug and Play Cloud Solution

- Megapixel CMOS image sensor
- Multiple H.264, Motion JPEG, MPEG-4 and 3GPP video streams
- 30 fps in 1920 x 1080
- 2.8mm, F2.0 megapixel fixed lens
- Two-way audio and built-in microphone
- MicroSD card slot storage
- Power over Ethernet (IEEE 802.3af)
- 1 x alarm input, 1 x alarm output
- RTC with built-in battery
- SSL v3 advanced HTTPS encryption
- Full support for Firefox, Safari, Chrome and Mac OS
- Supports Samba network storage
- 64-channel ZAVIO CamGraba NVR software
- 3GPP mobile surveillance
- Multi-lingual user interface
- ONVIF Compatible

Technical Specifications

Camera	
Models	D3200 Mini Dome IP Camera
Image sensor	1/2.7" progressive scan megapixel CMOS sensor
Lens	F2.0, 2.8mm
Angle of view	64° vertical, 107° horizontal, 120° diagonal
Digital zoom	10x digital
Min illumination	0.2 Lux at F2.0
Shutter time	1/2 ~ 1/10000 sec
Pan range	± 172°
Tilt range	± 79°
Rotation	± 180°
Video	
Video compression	Motion JPEG MPEG-4 part 2 (ISO/IEC 14496-2) simple profile H.264 baseline profile
Resolutions	Motion JPEG: 4 resolutions from 1920 x 1080 to 320 x 240 via API, 4 selections via configuration web page MPEG-4: 4 resolutions from 1920 x 1080 to 320 x 240 via API, 4 selections via configuration web page H.264: 4 resolutions from 1920 x 1080 to 320 x 240 via API, 4 selections via configuration web page
Frame rate	Motion JPEG: up to 30 fps at 1920 x 1080 MPEG-4: up to 30 fps at 1920 x 1080 H.264: up to 30 fps at 1920 x 1080
Video streaming	Simultaneous Motion JPEG, MPEG-4, H.264 and 3GPP (4 streams) Controllable Frame rate and bandwidth Support Unicast and Multicast Support 3GPP/ISMA RTSP (Real Time Streaming Protocol)
Image settings	Brightness, contrast, saturation WDR enhanced Rotation: mirror, flip, mirror flip Overlay capabilities: time, date, text and privacy Image
Audio	
Audio streaming	Two-way (full duplex)
Audio compression	G.711 μ law, a law, AMR
Network	
Security	Multiple user access levels with password protection, HTTPS encryption
Supported protocols	Bonjour, TCP/ IP, DHCP, PPPoE, ARP, ICMP, FTP, SMTP, DNS, NTP, UPnP, RTSP, RTP, HTTP, TCP,UDP, 3GPP/ ISMA RTSP
Users	10 simultaneous users Unlimited number of users using multicast
Alarm and Event Support	
Alarm input	Alarm input 5V DC
Alarm and event management	Input: alarm buffer, motion detection, audio detection Output: network storage, FTP, SMTP, pre-and post alarm buffer
System	
Connectors	RJ-45 Ethernet 10/ 100 Base-T Reset button 6pin cable for 1 alarm input, 1 output, 1 Line in, 1 Line out

Local storage	MicroSD card slot
General	
Casing	Top: PC+ABS casing; Bottom: Aluminum casing
Power	IEEE 802.3af PoE Class 1
Operating conditions	0 ~ 50 °C (32 ~ 122 °F)
Installation, management, and maintenance	ZAVIO camera management tool on CD and web-based configuration. Configuration of backup and restore firmware upgrades
Minimum web browsing requirement	Pentium 4 2.8GHz (or equivalent AMD) 256MB RAM graphic cards (or equivalent on-board graphic cards) 1G RAM Window 2000, 2003, XP, Vista or Windows 7 Mac OS Leopard 10.5 or later
Dimensions (HxWxD)	60.6 x 99 (φ)mm (2.4"x 3.9")
Weight	285g (0.63lb) excl. power supply
Included accessories	Quick Installation Guide, CD (IP Surveillance Software, Intelligent IP Installer, User Manuals, and Language Pack), mounting and connector kits, focus adjustment
Certification	CE, FCC, RoHS

Integration	
Video management software	IP Installer & Video management software-- ZAVIO CamGraba for viewing, recording and archiving up to 64 cameras

Physical Description

